

## HPL Framework Grounding Kit

**TSX-01S**

### Description

<b>Framework Body:</b>	EPDM + Stainless steel
<b>Grounding Cable:</b>	Copper (0.5m length)
<b>Compatibility:</b>	Matching with the cable with copper or Aluminium outer conductor



### Electrical Characteristics

<b>Impact Current Resistance:</b>	Grounding kit is able to bear or endure concussion current level reaching 70KA
<b>Contact Resistance:</b>	≤ 5 mΩ

### Mechanical & Environmental Characteristics

<b>Color:</b>	Black	
<b>Temperature:</b>	Operating	-50 °C / +85 °C
	Installation	-25 °C / +55 °C
	Storage	-50 °C / +50 °C
<b>Waterproof Index:</b>	IP68	
<b>RoHS Compliance:</b>	Yes	

### Type

Product number	Type	Approx. weight (g / p)
C0275S	1/4XF (φ6.85 × 500)	181
C1113S	1/4F (φ6.85 × 500)	181
C0270S	3/8XF (φ10.1 × 500)	181
C1114S	3/8F (φ10.1 × 500)	190
C2935S	1/2SF(φ13.4 × 500)	195
C0271S	1/2F (φ16 × 500)	188
C0272S	7/8F (φ27 × 500)	211
C0273S	1-1/4F (φ39.5 × 500)	233
C0274S	1-5/8F (φ50 × 500)	248